



TECHNICAL BULLETIN

DURA SEAL® WAX & CLEANER

PRODUCT DESCRIPTION:

A blend of cleaning agents and wax designed to remove scuff marks, light dirt, and grit while adding a soft sheen to waxed hardwood floors. Available in Neutral for light surfaces and Coffee Brown for dark surfaces.

WARNING! Removal of old paint by sanding, scraping, or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

RECOMMENDED USE: On waxed hardwood floors.

SURFACE PREPARATION: Remove dust and grit by sweeping or vacuuming.

DIRECTIONS:

1. Shake container well before use.
2. Using a cloth or a fine steel wool pad, spread Wax & Cleaner over the wood's surface at a coverage rate of 500 square feet per gallon.
3. Gently rub the surface to loosen dirt.
4. Wipe away loosened dirt and allow to dry 20-30 minutes. NOTE: Drying time will be increased by high humidity, low temperature or applying too heavily.
5. Polish with a clean cloth or polishing machine.

PRECAUTIONS:

Do not use on surfaces other than wood.
Do not use polyurethane over Wax & Cleaner.
Do not thin or adulterate.

COVERAGE: Approximately 500 square feet per gallon

CLEANUP: Clean equipment with mineral spirits or paint thinner.

MAINTENANCE: As necessary, remove dust and grit by sweeping or vacuuming. Wipe up spills as soon as possible. Periodic buffing will renew lustre. Exceptionally worn areas may occasionally require an additional coat of Wax & Cleaner.

SOLVENT: Nonphotochemically reactive

STORAGE: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame

PHYSICAL PROPERTIES

SOLVENT:	(NON-PHOTOCHEMICALLY REACTIVE)
PRODUCT WEIGHT (LBS/GAL):	6.9 (Typical)
% SOLIDS:	19.0 (Typical)
FLASHPOINT (SETA FLASH):	>101° F

SAFETY -HMIS RATING	Health	3
	Flammability	0
	Reactivity	0

PRODUCT LABEL PRECAUTIONS:

**CAUTION: COMBUSTIBLE MIXTURE, N.Y.F.D.C. OF A. NO.1187
KEEP OUT OF REACH OF CHILDREN.**

DANGER: Contains petroleum distillates and diacetone alcohol. Harmful or fatal if swallowed. Do not take internally. Avoid contact with skin and eyes. Wear rubber gloves and safety glasses when handling. Avoid inhalation and use only with adequate ventilation. If adequate ventilation cannot be maintained, wear respiratory protection (NIOSH/MSHA TC23C or equivalent) or leave the area. Do not use or store near heat, sparks, flame or other sources of ignition. Close container after each use.

FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. For skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention. In case of eye contact immediately flush eyes thoroughly with water, then remove any contact lenses. Continue to flush eyes with water for at least 15 minutes. If irritation persists, get medical attention. If affected by inhalation, immediately remove to fresh air. If symptoms persist, contact a physician.

COLOR	SIZE	SKU #	CASE/PACK
210 Neutral	Gallon	81410	6
223 Coffee Brown	Gallon	81423	6